



STANDARD FUNCTION		
Video	System	NTSC / PAL Video System and Video Loss Auto Detection
	Codec	MPEG4-SP ASF File Format
	Record Frame Rate	1, 2, ... , Maximum fps selectable Maximum: 30 fps@320x240 / 12 fps@640x480
	Record Quality	Low / Medium / High
	Recording Date/Time	Overlay with Video Images in ASF File
	Input	from built-in Camera
	Output	1 CH Composite Video Line Out
	Resolution	480TVL SONY CCD High Resolution
	Mini Illumination	0.001 LUX
	Lens	Wide Angle 104° 2.5mm Lens
Audio	Sampling Rate	44.1 KHz
	Codec	G.726/ 32 kbps
	Input	1 CH from built-in Microphone
	Output	1 CH Audio Line Out
Audio Device	Microphone,	
Storage Media	SD Card (FAT16/ up to 32GB) MAX FILES: 16384 FILES	
Serial Port	USB 1.1 (Read-Only)	
Recording Mode	Manual / Schedule (Alarm / Motion Detection / Continue)	
Motion Detection Setting	Multiple Blocks and adjustable sensitivity	
Event Search Function	Property and first image of selected file is displayed	
Playback Function	Play/Fast Forward/Fast Rewind/Pause/Step Forward/Step Backward	
Playback Speed	x1/ x2/ x4/ x8/ x16/ x32	
Power Supply	DC12V	
Dimensions	140mm (L) x 75mm (W) x 27mm(H)	
Operating Environment	30%~80% RH, 5°C ~ 45°C (41°F ~ 113°F)	
Storage Environment	30%~90% RH, 0°C ~ 50°C (32°F ~ 122°F)	

(Note: Design and Specifications are subject to change without notice.)