

Product Features :

- Outdoor / Indoor Camera
- High Impact IP66 Casing
- Wall / Ceiling Mountable
- 1/3 SONY CCD 480TVL 0 LUX
- Easily Adjustable IR 2.5~9mm Varifocal
- 36 High Intensity LEDs
- DC12V 450mA

**Video :**

Optical Technology Base:

Picture Elements (H x V in mm):

Horizontal Resolution:

Sync System:

Vertical Frequency:

Scanning System:

Mini Illumination:

Synchronization:

S/N Ratio:

Electronic Shutter

White Balance:

Lens:

Gamma Correction:

Auto Gain Control:

Video Output:

Operation Temperature:

Storage Temperature:

1/3" SONY CCD High Resolution

NTSC: 512(H) x 492(V)

PAL: 512(H) x 582(V)

480 lines

Internal

NTSC: 59.94Hz

PAL: 50Hz

2:1 Interlace

0 LUX (w/36 LEDs IR ON)

Internal

>48dB

up to 1/100.000sec.

ATW

2.5~9 mm Auto Iris Varifocal IR Lens

0.45

Auto

1Vp-p , 75 Ω

(-)10°C ~ (+)50°C

(-)30°C ~ (+)60°C

Physical:

Material:

Weight:

Metal

1.5lb - 680g

Power:

Power Supply:

Power Consumption:

DC12V (+/- 10%)

450mA